


NOTES

1. ALL BOXED DIMS ARE QUALITY CONTROL MEASUREMENTS
2. ALL DIMS IN BRACKETS ARE FOR REF. ONLY
3. PRECAST CONCRETE PIPE TO COMPLY WITH BS5911-1:2002.
4. CRACKS/ VOIDS/ STRAIGHTNESS/ SQUARE OF ENDS/ SURFACE FINISH AS PER BS 5911-1:2002.
5. POSN. AND QTY. OF GROUT/BENTONITE HOLES & PLUGS AS PER CUSTOMER ORDER.
6. SUPPLY AND FITMENT OF MDF PACKER IS A CUSTOMER OPTION.

STENCIL NOTE

- a) "Z" REPRESENTS THE CLASS OF PIPE AS PER BS5911-1:2002.
- b) "XXXX" REPRESENTS THE CHARACTERISTICS OF THE CONCRETE AS PER BS5911-1:2002.
- c) "YY YY YY" REPRESENTS THE DATE OF MANUFACTURE AS PER BS5911-1:2002.
- d) LETTERING NOT TO SCALE

ITEM	DESCRIPTION	QTY	DRG No.	MATERIAL	REMARKS
7	1 1/4" BSP NON-RETURN VALVE	2/3	BI-MS-0000-29	PLASTIC	ASS. POLYMER SERV.
6	1 1/4" BSP TAPER PLUG	2/3	BI-MS-0000-28	PLASTIC	CLEAN PLASTICS
5	1 1/4" BSP PARALLEL SOCKET	2/3	BI-MS-0000-30	STEEL	BRITISH FITTINGS
4	LOCLIFT ANCHOR 10A-115	2	BI-MS-0000-31	STEEL	SQUARE GRIP
3	COLLAR	1	AK-SC-2100-COLLAR	STEEL	BARHALE
2	INNER REO CAGE	1	AK-SC-2100x2500-LEAD-IC	STEEL	
1	OUTER REO CAGE	1	AK-SC-2100x2500-LEAD-OC	STEEL	

Rev	Date	Revision detail	By	Chkd
 FP McCann Alnwick, Little Houghton, Northumberland, NE66 3JX Tel: +44 (0) 1665 577653 Fax: +44 (0) 1665 577711 www.fpmccann.co.uk				
Contract: FP McCann Standard Jacking Pipe				
Title: DN2100 x 2500 Steel Collar Jacking Lead Pipe				
Scale:	1:15	Status:	For Manufacture	
Date:	May 2010	Drawn:	OOK	
Checked:		Rev:	A	
Drawing no:			AK-SC-2100x2500-LEAD-A	